



CELEBRATING *20* YEARS

PRODUCT COMPARISON GUIDE



» DESKTOP PRINTERS



MODEL		TDP-225	TDP-225W	TDP-244
Print method		DT	DT	DT
Print Resolution		203 dpi	203 dpi	203 dpi
Max. Print Area	Width	54 mm (2.13")	52 mm (2.05")	108 mm (4.25")
	Length	2,286 mm (90")	2,286 mm (90")	2,286 mm (90")
Max. Print Speed		5 ips (127 mm/sec.)	5 ips (127 mm/sec.)	4 ips (102 mm/sec.)
Memory	Flash	4 MB	4 MB	4 MB
	SDRAM	8 MB	8 MB	8 MB
SD/ microSD expansion Flash		4 GB	4 GB	4 GB
Media	Capacity	127 mm (5") OD	165 mm (6.5") OD	127 mm (5") OD
	Core	25.4 ~ 38 mm (1" ~ 1.5")	25.4 mm (1")	25.4 ~ 76.2 mm (1" ~ 3")
	Width	15 ~ 60 mm (0.59" ~ 2.36")	15 ~ 52 mm (0.59" ~ 2.05")	20 ~ 112 mm (0.78" ~ 4.4")
Ribbon	Capacity	N/A	N/A	N/A
	Core	N/A	N/A	N/A
	Width	N/A	N/A	N/A
Printer language		TSPL-EZ™	TSPL-EZ™	TSPL-EZ™
Real Time Clock		Standard	Standard	Factory Option
PHYSICAL FEATURES				
Dimension (W*H*D)		109 mm x 171 mm x 209 mm 4.29" x 6.73" x 8.23"	109 mm x 210 mm x 260 mm 4.29" x 8.27" x 10.24"	200 mm x 164 mm x 240 mm 7.87" x 6.46" x 9.45"
Weight		1.2 kg	1.2 kg	1.9 kg
INTERFACE				
Standard Interface		serial, USB 2.0	USB 2.0, Ethernet	USB 2.0
Optional Interface		Ethernet, Bluetooth, wireless	USB host	N/A
OPTIONS				
Factory Options		• 128 x 64 pixels graphic type LCD display with back light	• USB host, for scanner or PC keyboard	• Real time clock
Dealer Options		• Internal Ethernet interface (10/100 Mbps) • Peel-off module • Guillotine cutter (full cut and partial cut)	• Peel-off module • Guillotine cutter (full cut and partial cut)	• Peel-off module • Guillotine cutter (full cut or partial cut)
User Options		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard	N/A	• External roll mount, media OD. 214 mm (8.4") with 1" or 3" core • 3" core label spindle

* DT = Direct Thermal
* TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)



MODEL	TDP-247 SERIES	
	TDP-247	TDP-345
Print method		DT
Print Resolution		203 dpi
Max. Print Area	Width	108 mm (4.25")
	Length	2,286 mm (90")
Max. Print Speed		7 ips (178 mm/sec.)
Memory	Flash	4 MB
	SDRAM	8 MB
SD/ microSD expansion Flash		4 GB
Media	Capacity	127 mm (5") OD
	Core	25.4 ~ 76.2 mm (1" ~ 3")
	Width	20 ~ 112 mm (0.78" ~ 4.4")
Ribbon	Capacity	N/A
	Core	N/A
	Width	N/A
Printer language		TSPL-EZ™
Real Time Clock		Factory Option
PHYSICAL FEATURES		
Dimension (W*H*D)		200 mm x 164 mm x 240 mm 7.87" x 6.46" x 9.45"
Weight		1.9 kg
INTERFACE		
Standard Interface		serial, parallel, USB 2.0
Optional Interface		Ethernet, Bluetooth, wireless
OPTIONS		
Factory Options		• Internal Ethernet interface (10/100 Mbps) • Real time clock
Dealer Options		• Peel-off module • Guillotine cutter (full cut or partial cut)
User Options		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • External roll mount, media OD. 214 mm (8.4") on a 1" or 3" core • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard

» DESKTOP PRINTERS



MODEL		TTP-225 SERIES		TTP-243 PRO SERIES		
		TTP-225	TTP-323	TTP-243 PRO	TTP-243E PRO	TTP-342 PRO
Print method		DT/TT	DT/TT	DT/TT	DT/TT	DT/TT
Print Resolution		203 dpi	300 dpi	203 dpi	203 dpi	300 dpi
Max. Print Area	Width	54 mm (2.13")	54 mm (2.13")	104 mm (4.09")	104 mm (4.09")	104 mm (4.09")
	Length	2,286 mm (90")	1,016 mm (40")	2,286 mm (90")	2,286 mm (90")	1,016 mm (40")
Max. Print Speed		5 ips (127 mm/sec.)	3 ips (76 mm /sec.)	3 ips (76 mm /sec.)	3 ips (76 mm /sec.)	2 ips (51 mm /sec.)
Memory	Flash	4 MB		4 MB		
	SDRAM	8 MB		8 MB		
SD/ microSD expansion Flash		4 GB		4 GB		
Media	Capacity	127 mm (5") OD		Internal: 110 mm (4.33") OD External: 214 mm (8.42") OD		
	Core	25.4 ~ 38 mm (1" ~ 1.5")		25.4 ~ 76.2 mm (1" ~ 3")		
	Width	15 ~ 60 mm (0.59" ~ 2.36")		25.4 ~ 114 mm (1" ~ 4.49")		
Ribbon	Capacity	90 m, max.37 mm (1.46") OD		300 m, max. 67 mm (2.64") OD		
	Core	12.7 mm (0.5")		25.4 mm (1")		
	Width	56 ~ 58 mm (2.20" ~ 2.28")		40 ~ 110 mm (1.6" ~ 4.3")		
Printer language		TSPL-EZ™		TSPL, TPLE		
Real Time Clock		Standard		Standard (Except for TTP-243E Pro)		
PHYSICAL FEATURES						
Dimension (W*H*D)		140 mm x 177 mm x 241 mm 5.51" x 6.97" x 9.49"		232 mm x 156 mm x 288 mm 9.13" x 6.14" x 11.34"		
Weight		2.45 kg		2.5 kg		
INTERFACE						
Standard Interface		serial, USB 2.0		serial, USB 2.0		
Optional Interface		USB host, Ethernet, Bluetooth, wireless		parallel, Bluetooth, wireless		
OPTIONS						
Factory Options		• 128 x 64 pixels graphic type LCD display with back light • USB host, for scanner or PC keyboard		• Centronics parallel & RS-232 serial interfaces • Position centered gap sensor		
Dealer Options		• Internal Ethernet interface (10/100 Mbps) • Peel-off module • Guillotine cutter (full cut and partial cut)		• Rotary cutter (full cut)	N/A	• Rotary cutter (full cut)
User Options		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • SD Flash memory card reader • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard • External roll mount, media OD. 214 mm (8.4") with 1" or 3" core label spindle (only for TTP-243E Pro)		

* DT = Direct Thermal/ TT= Thermal Transfer
* TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)
* TPLE (Compatible to EPL II)



MODEL		TTP-244 PLUS	TA200 SERIES	
			TA200	TA300
Print method		DT/TT	DT/TT	DT/TT
Print Resolution		203 dpi	203 dpi	300 dpi
Max. Print Area	Width	108 mm (4.25")	108 mm (4.25")	104 mm (4.09")
	Length	2,286 mm (90")	2,794 mm (110")	1,016 mm (40")
Max. Print Speed		4 ips (102 mm/sec.)	4 ips (102 mm /sec.)	3 ips (76 mm /sec.)
Memory	Flash	4 MB	4 MB	
	SDRAM	8 MB	8 MB	
SD/ microSD expansion Flash		4 GB	4 GB	
Media	Capacity	110 mm (4.33") OD	127 mm (5") OD	
	Core	25.4 ~ 76.2 mm (1" ~ 3")	25.4 ~ 38 mm (1" ~ 1.5")	
	Width	25.4 ~ 112 mm (1.0" ~ 4.4")	25.4 ~ 118 mm (1.0" ~ 4.6")	
Ribbon	Capacity	300 m, max. 67 mm (2.64") OD	300 m, max. 67 mm (2.64") OD	
	Core	25.4 mm (1")	25.4 mm (1")	
	Width	40 ~ 110 mm (1.6" ~ 4.3")	40 ~ 110 mm (1.6" ~ 4.3")	
Printer language		TSPL-EZ™	TSPL-EZ™	
Real Time Clock		N/A	Standard	
PHYSICAL FEATURES				
Dimension (W*H*D)		232 mm x 156 mm x 288 mm 9.13"x 6.14"x 11.34"	224 mm x 186 mm x 294 mm 8.82" x 7.32" x 11.57"	
Weight		2.5 kg	2.45 kg	
INTERFACE				
Standard Interface		serial, USB 2.0	USB 2.0	
Optional Interface		parallel, Bluetooth, wireless	serial, parallel, Ethernet, Bluetooth, wireless	
OPTIONS				
Factory Options		• Centronics parallel & RS-232 serial interfaces	• RS-232 serial interface • 128 x 64 pixels graphic type LCD display with back light • Centronics parallel interface • Internal Ethernet interface (10/100 Mbps)	
Dealer Options		N/A	• Peel-off module • Guillotine cutter (full cut or partial cut)	
User Options		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • External roll mount, media OD. 214 mm (8.4") on a 1" or 3" core • SD Flash memory card reader • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard	• External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core • Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • 1.5" core adapter x 2 • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard	

» DESKTOP PRINTERS



MODEL		TTP-245C SERIES			TTP-247 SERIES	
		TTP-245C	TTP-343C	TTP-244CE	TTP-247	TTP-345
Print method		DT/TT	DT/TT	DT/TT	DT/TT	DT/TT
Print Resolution		203 dpi	300 dpi	203 dpi	203 dpi	300 dpi
Max. Print Area	Width	108 mm (4.25")	106 mm (4.17")	108 mm (4.25")	108 mm (4.25")	106 mm (4.17")
	Length	2,286 mm (90")	1,016 mm (40")	2,286 mm (90")	2,286 mm (90")	1,016 mm (40")
Max. Print Speed		6 ips (152 mm /sec.)	4 ips (102 mm /sec.)	4 ips (102 mm /sec.)	7 ips (178 mm /sec.)	5 ips (127 mm /sec.)
Memory	Flash	4 MB			4 MB	
	SDRAM	8 MB			8 MB	
SD/ microSD expansion Flash		4 GB			4 GB	
Media	Capacity	127 mm (5") OD			127 mm (5") OD	
	Core	25.4 ~ 38.1mm (1" ~ 1.5")			25.4 ~ 76.2 mm (1" ~ 3")	
	Width	20 ~ 112 mm (0.79" ~ 4.4")			20 ~ 112 mm (0.78" ~ 4.4")	
Ribbon	Capacity	110 m, max. 40 mm (1.57") OD			300 m, max. 67 mm (2.64") OD	
	Core	12.7 mm (0.5")			25.4 mm (1")	
	Width	40 ~ 110 mm (1.57" ~ 4.33")			40 ~ 110 mm (1.57" ~ 4.33")	
Printer language		TSPL-EZ™			TSPL-EZ™	
Real Time Clock		Factory Option (Standard in EMEA)			Factory Option	
PHYSICAL FEATURES						
Dimension (W*H*D)		202 mm x 173 mm x 258 mm 7.95"x 6.81"x 10.16"			213 mm x 188 mm x 314 mm 8.39"x 7.40"x 12.36"	
Weight		2.3 kg			2.8 kg	
INTERFACE						
Standard Interface		serial, parallel, USB 2.0, Ethernet		USB 2.0 (basic & advanced) serial, parallel, Ethernet (advanced)	serial, parallel, USB 2.0	
Optional Interface		Bluetooth, wireless		Bluetooth, wireless (advanced)	Ethernet, Bluetooth, wireless	
OPTIONS						
Factory Options		• Real time clock (standard in EMEA)		N/A	• Internal Ethernet interface (10/100 Mbps) • Real time clock	
Dealer Options		• Guillotine cutter (full cut or partial cut) • Peel-off module		• Guillotine cutter (full cut or partial cut) (advanced) • Peel-off module (advanced)	• Peel-off module • Guillotine cutter (full cut or partial cut)	
User Options		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • External media hanger with 3" OD label spindle • KP-200 Plus series keyboard • KU-007 Plus programmable smart keyboard		• External media hanger with 3" OD label spindle (basic & advanced) • Bluetooth module (serial interface) (advanced) • 802.11 b/g/n wireless module (serial interface) (advanced)	• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • External roll mount, media OD. 214 mm (8.4") on a 1" or 3" core • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard	

* DT = Direct Thermal/ TT= Thermal Transfer
* TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)

» INDUSTRIAL PRINTERS



MODEL		TTP-2410M PRO SERIES				
		TTP-2410M PRO	TTP-346M PRO	TTP-644M PRO	TTP-246M PRO	TTP-344M PRO
Print method		DT/TT	DT/TT	DT/TT	DT/TT	DT/TT
Print Resolution		203 dpi	300 dpi	600 dpi	203 dpi	300 dpi
Max. Print Area	Width	104 mm (4.09")	104 mm (4.09")	104 mm (4.09")	108 mm (4.25")	104 mm (4.09")
	Length	4,064 mm (160")	1,854 mm (73")	1,016 mm (40")	2,286 mm (90")	1,016 mm (40")
Max. Print Speed		12 ips (305 mm /sec.)	8 ips (203 mm /sec.)	4 ips (102 mm /sec.)	8 ips (203 mm /sec.)	6 ips (152 mm /sec.)
Memory	Flash	8 MB			4 MB	
	SDRAM	32 MB			8 MB	
SD/ microSD expansion Flash		4 GB				
Media	Capacity	208.3 mm (8.2") OD				
	Core	25.4 ~ 76.2 mm (1" ~ 3")				
	Width	25.4 ~ 118 mm (1" ~ 4.6")				
Ribbon	Capacity	600 m, max. 90 mm (3.54") OD				
	Core	25.4 mm (1")				
	Width	25.4 ~ 114.3 mm (1" ~ 4.5")				
Printer language		TSPL-EZ™				
Real Time Clock		Standard				
PHYSICAL FEATURES						
Dimension (W*H*D)		270 mm x 308 mm x 505 mm 10.63" x 12.13" x 19.88"				
Weight		15 kg				
INTERFACE						
Standard Interface		serial, parallel, USB 2.0, Ethernet, PS/2 keyboard			serial, parallel, USB 2.0	
Optional Interface		USB host, GPIO, bluetooth, wireless			Ethernet, PS/2 keyboard, USB host, GPIO, bluetooth, wireless	
OPTIONS						
Factory Options		• GPIO interface • USB host, for scanner or PC keyboard			N/A	
Dealer Options		• Internal rewinding kit (include internal rewind & label redirect front panel) • Peel-off kit (include internal rewind & peel off module)			• Internal rewinding kit (include internal rewind & label redirect front panel) • Peel-off kit (include internal rewind & peel off module) Multi-interface board : • Configuration 1: Internal Ethernet interface (10/100 Mbps) + PS/2 keyboard interface + SD Flash memory card reader • Configuration 2: USB host + Internal Ethernet interface (10/100 Mbps) + PS/2 keyboard interface + SD Flash memory card reader • Configuration 3: GPIO interface + USB host + Internal Ethernet interface (10/100 Mbps) + PS/2 keyboard interface + SD Flash memory card reader	
User Options		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • Regular cutter (full cut guillotine cutter) • Heavy duty cutter (rotary cutter)			• Care label cutter (rotary cutter) • KP-200 Plus series keyboard • KU-007 Plus programmable smart keyboard	

» INDUSTRIAL PRINTERS



MODEL		ME240 SERIES		TTP-268M SERIES		TTP-384M
		ME240	ME340	TTP-268M	TTP-366M	
Print method		DT/TT	DT/TT	DT/TT	DT/TT	DT/TT
Print Resolution		203 dpi	300 dpi	203 dpi	300 dpi	300 dpi
Max. Print Area	Width	104 mm (4.09")	104 mm (4.09")	168 mm (6.61")	168 mm (6.61")	219 mm (8.64")
	Length	2,286 mm (90")	1,016 mm (40")	14,732 mm (580")	6,604 mm (260")	5,080 mm (200")
Max. Print Speed		6 ips (152 mm /sec.)	4 ips (102 mm /sec.)	8 ips (203 mm /sec.)	6 ips (152 mm /sec.)	4 ips (102 mm /sec.)
Memory	Flash	4 MB		8 MB		8 MB
	SDRAM	8 MB		32 MB		32 MB
SD/ microSD expansion Flash		4 GB		4 GB		4 GB
Media	Capacity	203.2 mm (8") OD		208.3 mm (8.2") OD		208.3 mm (8.2") OD
	Core	25.4 mm ~ 76.2 mm (1" ~ 3")		76.2 mm (3")		76.2 mm (3")
	Width	25.4 ~ 118 mm (1.0" ~ 4.6")		50.8 ~ 172.7 mm (2" ~ 6.8")		101.6 ~ 241.3 mm (4" ~ 9.5")
Ribbon	Capacity	450 m, max. 81.3 mm (3.20") OD		450 m, max. 81 mm (3.19") OD		600 m, max. 90 mm (3.54") OD
	Core	25.4 mm (1")		25.4 mm (1")		25.4 mm (1")
	Width	40 ~ 110 mm (1.57" ~ 4.33")		50.8 ~ 178 mm (2" ~ 7.01")		110 ~ 254 mm (4.33" ~ 10")
Printer language		TSPL-EZ™		TSPL-EZ™		TSPL-EZ™
Real Time Clock		Standard		Standard		Standard
PHYSICAL FEATURES						
Dimension (W*H*D)		286 mm x 259 mm x 434 mm 11.26" x 10.20" x 17.09"		355 mm x 337 mm x 510 mm 13.98" x 13.27" x 20.08"		440 mm x 336 mm x 504 mm 17.32" x 13.23" x 19.84"
Weight		11 kg		23 kg		23.2 kg
INTERFACE						
Standard Interface		serial, USB 2.0		serial, parallel, USB 2.0, Ethernet, PS/2 keyboard		serial, parallel, USB 2.0, Ethernet, PS/2 keyboard
Optional Interface		parallel, USB host, Ethernet, Bluetooth, wireless		USB host, GPIO, bluetooth, wireless		USB host, GPIO, bluetooth, wireless
OPTIONS						
Factory Options		• Graphic type, 128 x 64 pixels LCD display • Internal Ethernet interface (10/100 Mbps) • USB host, for scanner or PC keyboard • Centronics parallel interface		• GPIO interface		• GPIO interface • USB host, for scanner or PC keyboard
Dealer Options		• Peel-off module • Guillotine cutter (full cut)		• Peel-off kit (include internal rewind & peel off module) • Heavy duty cutter (full cut)		N/A
User Options		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard		• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard		• Guillotine cutter (full cut) • Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard

* DT = Direct Thermal/ TT= Thermal Transfer
* TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)

» PORTABLE PRINTERS



MODEL		ALPHA-3R	ALPHA-4L
Print method		DT	DT
Print Resolution		203 dpi	203 dpi
Max. Print Area	Width	72 mm (2.83")	104 mm (4.09")
	Length	2,286 mm (90")	2,286 mm (90")
Max. Print Speed		4 ips (102 mm /sec.)	4 ips (102 mm /sec.)
Memory	Flash	4 MB	16 MB
	SDRAM	8 MB	32 MB
SD/ microSD expansion Flash		N/A	4 GB
Media	Capacity	Receipt: 57 mm (2.25") OD Label (selected): 55 mm (2.16") OD	67.3 mm (2.65") OD
	Core	10.2 ~ 25.4 mm (0.4" ~ 1")	12.7 ~ 25.4 mm (0.5" ~ 1")
	Width	Receipt: 50.8 ~ 80 mm (2" ~ 3.15") Label (selected): 50.8 ~ 78 mm (2" ~ 3.07")	50.8 ~ 112 mm (2.0" ~ 4.4")
Drop Specification		1.5 m (5 ft)	1.5 m (5 ft) 1.8 m (6 ft) (w/ case)
IP rating		IP54 (w/case)	IP54 (w/case)
Power		7.4V DC, 2500 mAh Li-ion rechargeable battery	7.2V DC, 5800 mAh Li-ion rechargeable battery
Printer language		TSPL-EZ™ or CPCL	TSPL-EZ™ or CPCL
Real Time Clock		N/A	Standard
PHYSICAL FEATURES			
Dimension (W*H*D)		116 mm x 148 mm x 70 mm 4.57" x 5.83" x 2.75"	160 mm x 191.6 mm x 79 mm 6.30" x 7.54" x 3.11"
Weight		0.55 kg	1.1 kg
INTERFACE			
Standard Interface		USB 2.0	USB 2.0, Bluetooth
Optional Interface		serial, Bluetooth, wireless	serial, wireless
OPTIONS			
Factory Options		• 802.11 b/g/n wireless network • Bluetooth module	• 802.11 b/g/n wireless network • 2" LCD display, 128 x 64 pixel w/white LED backlight • Black mark reflective sensor position (default center, right, or left side) • Linerless kit and standard label peel mechanism
Dealer Options		N/A	N/A
User Options		• USB to RS-232 converter cable • USB cable • Li-ion battery • Charge station 1 cell (with changeable power connector) • Vehicle power adapter • IP54-rated protective case with shoulder strap	• USB to RS-232 converter cable • USB cable • Li-ion battery • IP54-rated protective case • Shoulder strap • Charging station 1 cell or 4 cells (with changeable power connector) • Vehicle power adapter

Asia Pacific

TAIWAN (CORPORATE HEADQUARTERS)

TSC Auto ID Technology Co., Ltd.

9F., No.95, Minquan Rd., Xindian Dist.
New Taipei City 231
Taiwan (R.O.C.)

Tel: +886 2 2218 6789
E-mail: printer_sales@tscprinters.com
Technical Support: tech_support@tscprinters.com

TAIWAN (LI ZE PLANT)

TSC Auto ID Technology Co., Ltd.

No.35, Sec. 2, Ligong 1st Rd.
Wujie Township, Yilan County 268
Taiwan (R.O.C.)

Tel: +886 3 990 6677
E-mail: printer_sales@tscprinters.com
Technical Support: tech_support@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.

2F., No. 165, Huang Hai Rd.
Tianjin Economic-Technologic Development Area
Tianjin 300457
China

Tel: +86 22 5981 6661
E-mail: sale@tscprinters.com.cn
Technical Support: support@tscprinters.com.cn

INDIA

TSC India Representative Office

F/701, Sterling, Mohan Heights
Khadakpada , Kalyan West - 421302
Maharashtra
India

Tel: +91 9987 131 874
E-mail: printer_sales@tscprinters.com
Technical Support: tech_support@tscprinters.com

Americas

USA (CORPORATE OFFICE)

TSC Auto ID Technology America Inc.

3191 West Temple Avenue, Suite #105
Pomona, CA 91768
U.S.A.

Tel: +1 909 525 9779
E-mail: sales@tscprinters.com
Technical Support: service@tscprinters.com

USA (BRANCH OFFICE)

8810 Commodity Circle, Suite #35
Orlando, FL 32819
U.S.A.

Tel: +1 407 704 8918
E-mail: sales@tscprinters.com
Technical Support: service@tscprinters.com

MEXICO

TSC Mexico Representative Office

idc-COMPONENTES S.A. de C.V.
Carretera Base Aérea Militar 5850 int. 8
Zapopan, Jalisco CP 45019
Mexico

Tel: +52 (33) 3836 6682
Sales Inquiry: sales@idc-componentes.com
Warranty Repair: tscwarranty@idc-componentes.com

BRAZIL

TSC Brazil Representative Office

Rua Aurea 277, Vila Mariana
Sao Paulo-SP
Brazil

Tel: +55 (11) 9597 8098
E-mail: sales@tscprinters.com
Technical Support: service@tscprinters.com

Europe, Middle East and Africa

GERMANY (CORPORATE OFFICE)

TSC Auto ID Technology EMEA GmbH

Georg-Wimmer-Ring 8b
85604 Zorneding
Germany

Tel: +49 (0) 8106 37979 00
E-mail: info@tsceu.com
Technical Support: service@tsceu.com

RUSSIA

TSC Auto ID Technology EMEA GmbH

19 Leninskaya Sloboda St.
115280 Moscow
Russia

Tel: +7 495 249 9017
E-mail: info@tsceu.com
Technical Support: service@tsceu.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd., FZE

DAFZA
Building 7WA/ West Wing
Office Number - G009
Dubai, UAE

Tel: +971 4 2533 069
E-mail: info@tscmea.com
Technical Support: service@tsceu.com

