

SNBC

Extraordinary
Value!

BTP-2002NP

Thermal Receipt Printer



Advanced High Speed Versatile Printer

The BTP-2002NP thermal receipt printer is a low-cost high quality transaction printer produced by SNBC – a leading manufacturer of thermal print heads. The heavy-duty metal frame makes the BTP-2000NP thermal printer ideal for rugged environments.

- 200mm per Second Print Speed
- Serial, Parallel, USB, Ethernet and Wireless WiFi Interface Options
- Prints Watermark
- Stores and Prints Logo Images
- Extraordinary Reliability
- Everything Needed – Including Communications Cable – Included in the Box



SNBC BTP-2002NP Thermal Receipt Printer



Drop and Print Paper Loading with Built-In Paper Width Selector



Standard Cable Management Cover / Optional Power Supply Cover & Spill Cover



Optional Audio/Visual Print Messenger and Optional Wall Mount Bracket



Includes Everything Necessary in the Carton

Features

A low-cost high quality thermal receipt printer ideal for rugged environments.

- Everything You Need is in the Box
- Serial, Parallel, USB, Ethernet or Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Other SNBC Printers
- Auto-Cutter with Selectable Full or Partial Cut
- Stores/Prints Logo Images
- Prints Watermark
- Fast 200mm per Second Print Speed
- Drop and Print Paper Loading
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches – Intuitive Keypad Programming
- Includes Starter Paper Roll, Paper Width Selector, Communications Cable, Power Adapter and Cord, Cable Cover, CD-ROM with Drivers, Utilities and User's Manual

Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Serial, Parallel, USB, Ethernet and Wireless WiFi Interface Boards Are User Interchangeable
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed
- Powered USB Cable
- Wall Mount Bracket
- Spill Cover
- Power Supply Cover

Ports and Connectivity

- A Choice of Serial (Shown), Parallel, USB, Ethernet or Wireless WiFi Interface Boards Available
- B Cash Drawer
- C DC 24V Power-In

Specifications

Print Speed:	200mm per Second / 63 Lines per Second
Characters Per Line –	Font A: 42 (80mm) / 37 (58mm) Font B: 56 (80mm) / 49 (58mm)
Characters Size –	Font A: 12 x 24 Font B: 9 x 17
Paper Roll Type –	Width: 82.5±0.5mm, 80.0±0.5mm, 76.0±0.5mm, 69.5±0.5mm, 57.5±0.5mm Maximum Diameter: 83mm
Reliability –	MTBF: 348,000 Hours MCBF: 52,000,000 Lines Printhead Life: 100,000,000 Characters Cutter Life: 1,500,000 Cuts
Character Set:	Alphanumeric: 95 International: 37
Extended Graphic:	128 x 11 Page
Bar Code:	UPC-A / UPC-E / EAN8 / EAN13 / CODABAR / Code39 / ITF / Code128 / Code93 / PDF417
Interpreter:	ESC/POS™
Interface:	Serial / Parallel / USB / Ethernet / Wireless WiFi
Driver:	Windows 98 / NT4.0 / 2000 / 2003 / XP / VISTA
Drawer Port:	One RJ-12 (+24VDC) (Maximum 2 Drawers – Supports Open/Close)
Data Buffer –	Receive Buffer: 4 KB RAM Selectable to 64 KB NV Bit Image Data: 128 KB User NV Memory: 1 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included
Current/Power Usage:	2.5A / 60W
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)
Operating Humidity:	20% ~ 90% RH (Non-Condensing)
Paper Cutting Method:	Auto-Cutter with Selectable Full or Partial Cut
Dimensions:	5-3/4"W x 5-11/16"H x 7-5/8"D
Weight:	5.08 lbs.
Safety and EMI:	FCC, UL, CUL, CE, CB, GS, RoHS

